80 PLUS Verification and Testing Report

TYPICAL EFFICIENCY (50% Load):	85.95%
AVERAGE EFFICIENCY:	84.26%
80 PLUS COMPLIANT:	YES



0.012

-Current

10

5

0

-5

-10

Input Current and Voltage Waveforms

0.006

200 150

100 Voltage (V)

50 0


-50

-100

-150

ID#	1824.2
Manufacturer	LC-Power
Model Number	LC8550 V2.31 Prophet
Serial Number	N/A
Year	2009
Туре	ATX12V
Test Date	12/10/2009

Rated Specifications	Value	Units
Input Voltage	110-240	Volts
Input Current	10-6	Amps
Input Frequency	60-50	Hz
Rated Output Power	550	Watts





Time (s)

- Voltage

Rated Opcomeditions	Value	Office		
Input Voltage	110-240	Volts		
Input Current	10-6	Amps		
Input Frequency	60-50	Hz		
Rated Output Power	550	Watts		
Note: All measurements were taken with input voltage at 115	V nominal and 60 Hz			

I _{RMS}	PF	I _{THD} (%)	Load	Fraction	Input	DC Terminal Voltage (V)/ DC Load Current (A)				Output	Efficiency	
Α			(%)	of Load	Watts	12V (cumulative of 12V1, 12V2, etc.)	-12V	3.3V	5V*	5VSB	Watts	%
1.23	0.95	28.47%	20%	Light	134.83	12.5/6.4	12.2/0.1	3.3/3.5	5.1/3.7	5.1/0.5	113.40	84.10%
2.98	0.95	30.83%	50%	Typical	326.80	12.4/16.1	12.2/0.2	3.3/9.3	5.1/8.6	5/1.2	280.87	85.95%
6.03	0.97	23.65%	100%	Full	674.60	12.4/32.1	12.3/0.3	3.3/18.4	5/17.2	4.9/2.3	558.04	82.72%







PLUG LOAD
These tests were conducted by a third party independent testing firm on behalf of the 80 PLUS Program. 80 PLUS is a certification program to promote highly-efficient power supplies (greater than 80% efficiency in the active mode) in technology applications. http://www.80plus.org/

