## **80 PLUS Verification and Testing Report**

TYPICAL EFFICIENCY (50% Load):	
AVERAGE EFFICIENCY :	
80 PLUS COMPLIANT:	



Input Current and Voltage Waveforms

0.003 0.006

20 15

10

5

0

-5 -10

Current (A)

200

150 100

50

-50

-100

0

Voltage (V)

1274.2
XILENCE
XP1200.XQ
N/A
2009
ATX12V
1/23/2009

Rated Specifications	Value	Units
Input Voltage	100-240	Volts
Input Current	15	Amps
Input Frequency	50-60	Hz
Rated Output Power	1200	Watts

Note: All measurements were taken with input voltage at 115 V nominal and 60 Hz.

-150 -15							
-200							
Time (s)							

0.009

Input AC Current Waveform (ITHD = 8.88%, 50% Load)

0.012 0.01

I <sub>RMS</sub>	PF	I <sub>THD</sub> (%)	Load	Fraction	Input	DC Terminal Voltage (V)/ DC Load Current (A)					Output	Efficiency
Α			(%)	of Load	Watts	12V (cumulative of 12V1, 12V2, etc.)	-12V	3.3V	5V*	5VSB	Watts	%
2.48	0.96	17.4%	20%	Light	274	12.2/17.6	12/0.1	3.3/3.2	5.2/3.1	5/0.5	245	89.41%
5.91	0.99	8.9%	50%	Typical	672	12.2/43.8	12/0.2	3.3/7.9	5.2/7.9	5/1.3	611	90.84%
12.07	1.00	5.2%	100%	Full	1383	12.2/87.6	12.1/0.4	3.3/15.7	5.1/15.8	5/2.6	1216	87.92%

90.84% 89.39% YES







These tests were conducted by a third party independent testing firm on behalf of the 80 PLUS® Program. 80 PLUS is a certification program to promote highly-efficient power supplies (greater than 80% efficiency in the active mode) in technology applications. http://www.80plus.org/

